Get Started

Common Crawl data is free to access by anyone from anywhere.

The data is hosted by **Amazon Web Services' Open Data Sets Sponsorships** program. You can find the data in the `commoncrawl` bucket, located in the `us-east-1` (Northern Virginia) Region.

You may process the data in the AWS cloud or download it to your own HTTP(S) edge or internal infrastructure.

Choose a crawl...

The canonical location for data in the AWS cloud is `s3://commoncrawl/`; however, we recommend using the HTTPS data access endpoint, `https://data.commoncrawl.org/`, which is fronted by the Amazon CloudFront global content delivery network.

To access data from outside the Amazon cloud, via HTTPS, you can use `https://data.commoncrawl.org/` or `https://commoncrawl.s3.amazonaws.com/`.

For further detail on the data file formats listed below, please see the **ISO Website**, which provides formal standards, information and supporting materials. There are also helpful explanations and detailed examples available on the Library of Congress website.

The status of our infrastructure can be monitored on our **Info Status** page.

Accessing the data in the AWS Cloud

It's mandatory to access the data from the Amazon Web Services (AWS) cloud in region `us-east-1`.

The connection to S3 should be faster and you avoid the minimal fees for inter-region data transfer. Also, you don't incur bandwidth fees which are charged on outgoing traffic.

You can provision an Elastic IP address or load balancer, because you may be charged for the hosted traffic.

You may use the **AWS Command Line Interface** but many AWS services (e.g. EMR) support "`s3://`" paths natively, and can access Common Crawl data directly. For example, `aws s3 ls s3://commoncrawl/crawl-data/CC-MAIN-2013-20/`.

On Hadoop (not EMR) it's recommended to use the **S3A Protocol** and change the paths accordingly.

Accessing the data from outside the AWS Cloud

If you want to download the data to your local machine or local clusters you can use HTTP download utilities such as **cURL** or **wget**. The data is available on `https://data.commoncrawl.org/` and `https://commoncrawl.s3.amazonaws.com/` URL schema.

Therefore, we need to create an AWS account in order to access the data using this method.

Using the AWS Command Line Interface

The **AWS Command Line Interface** can be used to download individual files or file sets from Common Crawl. Please follow the **installation instructions**.

Please note, access to data from the Amazon Cloud uses always the S3 API is only allowed for authenticated users. Please see our **blog announcement** for more information.

Once the AWS CLI is installed, the command to copy a file to your local directory is:

```
aws s3 cp
s3://commoncrawl/path_to_file
./local_path/
```

You may first look at the data e.g. to list all **WARC** files of a particular crawl archive from 2013:

```
$ aws s3 ls s3://commoncrawl/crawl-data/CC-MAIN-2013-20/segments/1368696381249/warc/
2013-05-18 05:33:20 956184811 CC-MAIN-20130516092621-00000-ip-10-60-113-184.ec2.internal.warc.gz
2013-05-18 05:33:20 973528962 CC-MAIN-20130516092621-00001-ip-10-60-113-184.ec2.internal.warc.gz
2013-05-18 05:33:20 914933736 CC-MAIN-20130516092621-00002-ip-10-60-113-184.ec2.internal.warc.gz
...
```

The command to download the first file in the listing is:

```
aws s3 cp s3://commoncrawl/crawl-data/CC-MAIN-2013-20/segments/1368696381249/warc/CC-MAIN-20130516092621-00000-ip-10-60-113-184.ec2.internal.warc.gz ./
```

The AWS CLI supports recursive copying, and allows wild-card filtering for inclusion/exclusion of files.

For more information please see the AWS CLI user guide or call the command-line help from the file system:

```
aws s3 cp help
```

Using HTTP/S download agents

To download a file using an HTTP download agent add the full path to the prefix `https://data.commoncrawl.org/`, e.g.

```
wget
https://data.commoncrawl.org/crawl-data/CC-MAIN-2013-20/segments/1368696381249/warc/CC-MAIN-20130516092621-00000-ip-10-60-113-184.ec2.internal.warc.gz
```

Example Code

If you're more interested in diving into Code, we've provided **Introductory Examples** for Java, Python and Hadoop frameworks to process the data, and many more in our **Tutorials Section** and on **GitHub**.

```
import requests
import gzip
import io

# For warcio, WARC
# from warcio.archiveiterator import ArchiveIterator

# For gzipped WAT Records
# from warcio.archiveiterator import WARCIterator

# Path to one of the Common Crawl Index Server
# Example path for CC-MAIN-2018-22 crawl
path = 'cc-index/collections/CC-MAIN-2018-22/indexes/cdx-00188.gz'

# Base URL for HTTP requests to the Common Crawl data
# This is a public server, so no authentication is required
base_url = 'https://data.commoncrawl.org/'

# Function to search the Common Crawl Index Server
def search_cc_index(url):
    # Construct the URL for the Index Server query
    index_url = f'{base_url}{path}'
    # Send a GET request to the Index Server
    response = requests.get(index_url, stream=True)
    # Check if the request was successful
    if response.status_code == 200:
        # Decompress the gzipped response
        with gzip.GzipFile(fileobj=response.raw) as gz_file:
            # Read the decompressed data line by line
            for line in io.TextIOWrapper(gz_file, encoding='utf-8'):
                # Check if the line contains the URL we're searching for
                if url in line:
                    # Print the matching line (contains JSON data)
                    print(line.strip())
    else:
        print(f'Error: Received status code {response.status_code}')

# Example usage
search_cc_index('example.com')
```

Data Types

Common Crawl currently stores the crawl data using the **WARC Format**. Previously stored in the format **ARC** (see the **ARC Format** and **WARC Format**).

The **WARC** format allows for more efficient storage and processing of Common Crawl's own crawls and other crawls in the future. The WARC format contains exactly the raw data crawled. We store three different types of records in the WARC files.

If you want all the utility-data, please see the **Introduction to the WARC Standard**.

Click the points below for an overview of the different types.

WARC files which store the raw crawl data. This is the primary data set and contains all the data stored in the **WARC** format.

WET files which contain extracted plaintext from the data stored in the **WARC**.



The **WARC** format is the raw data from the crawl, providing a direct mapping to the crawl process.

Not only does the format store the HTTP request and response from the web server, but it also stores information about the machine performing the request and how the information was requested in detail. More detailed information can be found in the crawl process itself (**WARC**) type metadata.

For the HTTP responses themselves, the raw response is stored. This not only includes the response payload, but all the HTTP headers and it's also stored exactly as downloaded. The fact also the HTTP headers are preserved, which can be used to glean a number of interesting insights.

In the example below, we can see the crawler contacted `https://en.wikipedia.org/wiki/Tarantula` and received HTML in response.

You can also see the page uses caching details, and attempts to set a cookie (denoted by the `Set-Cookie` field).

See the full WARC extract

```
WARC/1.0
warc-type: response
warc-target-uri: https://en.wikipedia.org/wiki/Tarantula
warc-date: 2017-03-06T04:08:08Z
warc-identified-payload-type: text/html
warc-ip-address: 208.80.154.224
warc-record-id: <urn:uuid:83c1e3ec-0c8f-4bf9-a459-8a8e79d5b463>
warc-block-digest: sha1:PYRBJ3LJ6HMMYNSPM3DSMVCB7Z2JQZAY
warc-payload-digest: sha1:B2LTWWPUOYAH7UIPQ7ZUPQ4VMBSVC36A
content-type: application/http; msg type=response
content-length: 56699

HTTP/1.1 200 OK
Server: mw1239.eqiad.wmnet
X-Content-Type-Options: nosniff
Content-Language: en
Vary: Accept-Encoding,Cookie
Last-Modified: Wed, 01 Mar 2017 12:00:00 GMT
Content-Type: text/html; charset=UTF-8
X-Cache: cp1066 miss, cp2021 miss
Cache-Control: private, s-maxage=0, max-age=0, must-revalidate
Date: Mon, 06 Mar 2017 04:08:08 GMT
Connection: keep-alive
Set-Cookie: GeoIP=US:CA:San_Francisco:37.77:-122.42:v4; Path=/; domain=.wikipedia.org
Set-Cookie: WMF-Last-Access=06-Mar-2017; Path=/; HttpOnly; secure; Expires=Wed, 05 Apr 2017 00:00:00 GMT
Set-Cookie: WMF-Last-Access-Global=06-Mar-2017; Path=/; HttpOnly; secure; Expires=Wed, 05 Apr 2017 00:00:00 GMT
Set-Cookie: NetworkProbeLimit=0.001; Path=/; HttpOnly; secure; Expires=Mon, 06 Mar 2017 04:13:08 GMT
X-Client-IP: 192.0.2.1
Age: 0
X-Cache-Status: pass
Server-Timing: cache;desc="pass", host;desc="mw1239"
Strict-Transport-Security: max-age=106384710; includeSubDomains; preload
Set-Cookie: WMF-DP=ccc;Path=/;HttpOnly;secure;Expires=Mon, 13 Mar 2017 00:00:00 GMT
X-Analytics: ns=0;page_id=4233;WMF-Last-Access=06-Mar-2017;WMF-Last-Access-Global=06-Mar-2017;https=1;nocookies=1
X-Client-IP: 192.0.2.1
Cache-Control: private, s-maxage=0, max-age=0, must-revalidate
Set-Cookie: GeoIP=US:CA:San_Francisco:37.77:-122.42:v4; Path=/; domain=.wikipedia.org
Set-Cookie: WMF-Last-Access=06-Mar-2017; Path=/; HttpOnly; secure; Expires=Wed, 05 Apr 2017 00:00:00 GMT
Set-Cookie: WMF-Last-Access-Global=06-Mar-2017; Path=/; HttpOnly; secure; Expires=Wed, 05 Apr 2017 00:00:00 GMT
Set-Cookie: NetworkProbeLimit=0.001; Path=/; HttpOnly; secure; Expires=Mon, 06 Mar 2017 04:13:08 GMT
X-Client-IP: 192.0.2.1
Age: 0
X-Cache-Status: pass
Server-Timing: cache;desc="pass", host;desc="mw1239"
Strict-Transport-Security: max-age=106384710; includeSubDomains; preload
Set-Cookie: WMF-DP=ccc;Path=/;HttpOnly;secure;Expires=Mon, 13 Mar 2017 00:00:00 GMT
X-Analytics: ns=0;page_id=4233;WMF-Last-Access=06-Mar-2017;WMF-Last-Access-Global=06-Mar-2017;https=1;nocookies=1
<!DOCTYPE html>
<html class="client-nojs" lang="en" dir="ltr">
<head>
<meta charset="UTF-8"/>
<title>Tarantula - Wikipedia, the free encyclopedia</title>
<script>document.documentElement.className="client-js";RLCONF={"wgBreakFrames":false,"wgSeparatorTransformTable":["",""],"wgDigitTransformTable":["",""],"wgDefaultDateFormat":"dmy","wgMonthNames":["","January","February","March","April","May","June","July","August","September","October","November","December"],"wgRequestId":"WHzHwAoAIDIAAH1ZFwQAAABJ"};
...
```


© 2025 Common Crawl